


E21 Extrusion

Linear aluminium LED extrusion, circular in section, suitable for surface mounting and offered in 3 light output levels. The profile has a rotate and fix facility for setting at the optimum uniform position. The extrusion can also be supplied in made to measure lengths. An opal diffuser ensures constant illumination without spotting or shadow lines.

- Rotate & fix facility
- Samsung single bin chip
- up to 1516 lm/m, efficacy 85 lm/w
- 4oz PCB for optimum heat distribution and longevity
- Phase, 1-10V or Dali Dimmable



LED type	Samsung LM281B
Efficacy	Up to 85 lm/w
Luminaire luminous flux (LLF)	Up to 1516 lm/m
CRI (typical)	80+
Bin code	Single bin
LED lifetime	50,000hrs L70
Control Gear	Remote (included)

Power	Diffuser	CCT (°K)	LLF (lm)
5W/m	Opal	2700	466
		3000	507
		3500	508
		4000	531
10W/m		2700	895
		3000	975
		3500	977
		4000	1040
15W/m		2700	1295
		3000	1412
		3500	1413
		4000	1516

LLF - Luminaire Luminous Flux

Product Variants: E21-

Example Code: E21-15W-O-40-RAL-1985-P

Power	Diffuser	CCT (°K)	Finish	Length	Driver
5W/m 5W	Opal O	2700 27	Ano Alu A	Enter Length L	Non Dim ND
10W/m 10W		3000 30	RAL RAL		1-10V T
15W/m 15W		3500 35			Dali D
		4000 40			Phase P

NB Compatibility of the phase dimmer and driver must be checked prior to order